

MINIMIZED SNIPE PLANER SERIES

Geetech 20" Planer powered by a three horsepower induction motor is a high precision, high quality designed tool to meet the demands on the market. Its feeding speeds 16FPM and 20FPM offer users to select from two different speeds. In addition, the oil bath lubricated gear gives powerful and smooth feeding processes.

The fixed robust Cast Iron Table with extended Cast Iron Wings add up to 51" in total length and 20" width dimensions, allowing users load lengthy and extended stocks. Not only Nitrogen Cylinder elevation mechanism supports easy crank up and down, the two Rollers located on top of the Cast Iron Head provide convenient handling for consecutive cutting operation.

20" PLANER

SPECIFICATIONS	
Induction Motor	3HP 230V 60HZ 1ψ
Max. Depth of Cut	1/8"
Max. Stock Thickness	8"
Max. Cutting Width	20"
Min. Stock Thickness	1/4"
Min. Stock Length	7"
Feed Speed	16/20FPM
Cutterhead RPM	5,000
Cutterhead Diameter	3 1/4"
Number of Blades	4
Spiral Cutterhead	3 / 4 / 5 rows (Optional)
Built-in Mobile Wheels	√
Dust Port Diameter	5"
Net Weight	860lbs / 390kgs

FEATURES	
Fixed Cast Iron Table allowing extended workpiece at any length	
Table Dimensions: 20"x21"	
Table with extended wings up to 51" in length	
Oil bath lubricated gear for longer gear life and powerful feeding	
Nitrogen Cylinder elevation for effortless crank up and down	
Auto Depth Lock function	
Two Top Rollers for convenient consecutive cutting operation	

Minimized Snipe!
Below 0.002"/0.05mm



15" PLANER

15" Planer

Image

Pending

FEATURES		SPECIFICATIONS	
Fixed Cast Iron Table allowing extended workpiece at any length		Induction Motor	3HP 230V 6HZ 1ψ
Table Dimensions: 15"x20"		Max. Depth of Cut	1/8"
Table with extended wings up to 48" in length		Max. Stock Thickness	6"
Oil bath lubricated gear for longer gear life and powerful feeding		Max. Cutting Width	15"
Nitrogen Cylinder elevation for effortless crank up and down		Min. Stock Thickness	3/16"
Auto Depth Lock function		Min. Stock Length	6"
		Feed Speed	16/20FPM
		Cutterhead RPM	5,000
		Cutterhead Diameter	3"
		Number of Blades	3
		Spiral Cutterhead	3 / 4 / 5 rows (Optional)
		Built-in Mobile Wheels	√
		Dust Port Diameter	4"
		Net Weight	407.9lbs / 185kgs

Optional Wixey DRO

CSA and UL Certified

